



Not to scale.



Features & Benefits

- Adjustable depth control prevents overdrive of washers
- Available with collated screws up to 3" in length
- Available corded or cordless
- Patented and/or patent pending

PRODUCT DESCRIPTION

The Grip-Lok® Auto-Feed System is used to attach exterior gypsum sheathing, building wrap, continuous insulation, and lath to wood or steel studs. It is a convenient tool for installing Thermal-Grip® ci prong washers or Plasti-Grip® ci prong washers for rapid attachment of insulation to steel or wood studs.

PRODUCT SELECTION



Part No.	Description	Pkg. Qty.	Pkg. Wt.
A-W-DS322	SENCO DS322 Gun w/ Stem - Battery	1	15
A-W-DS332C	SENCO DS332 Gun w/ Stem - Corded	1	12
BIT-PH2-8000SC	SENCO #2 Phillips Bit - 2 Pack	1	1

	Part No.	Part Length	Pkg. Qty.	Pkg. Wt.	Packaging Type
Grip-Deck® Self-Drilling Screws	FSD06C-1625	#6 x 1-5/8"	1000 pcs.	6 lbs.	Collated*
	FSD06C-2000	#6 x 2"	1000 pcs.	6 lbs.	Collated*
	FSD08C-2500	#8 x 2-1/2"	1000 pcs.	10 lbs.	Collated*
	FSD08C-3000	#8 x 3"	1000 pcs.	12 lbs.	Collated*



	Part No.	Part Length	Pkg. Qty.	Pkg. Wt.	Packaging Type
Grip-Deck® Hi-Lo Screws	FHL07C-1625	#7 x 1-5/8"	1000 pcs.	6 lbs.	Collated*
	FHL07C-2000	#7 x 2"	1000 pcs.	7 lbs.	Collated*
	FHL08C-2500	#8 x 2-1/2"	1000 pcs.	10 lbs.	Collated*
	FHL08C-3000	#8 x 3"	1000 pcs.	12 lbs.	Collated*



Bulletin No. TFW-24033

DISCLAIMER

The information provided here is subject to change without notice. The performance specifications published in this TRUFAST® Walls product literature are based on controlled laboratory tests and are intended as a guideline only. They are not guaranteed in any way by the ALTENLOH, BRINCK & CO. US, INC., since building

design, engineering, and construction, including workmanship and materials, are beyond the control of the manufacturer. The manufacturer recommends that pull-out tests be conducted to verify the substrate provides adequate pull-out values.